

- 4MP Vari-focal IR Dome Network Camera
- GW-HDB78RC84-FP



Features

- 1/3" Progressive Scan CMOS
- 4MP HD resolution 2560 x 1440 output
- Ultra low illumination 0.01Lux
- Day/Night (ICR), AWB, AGC, D-WDR, 2D/3D-DNR, IR-CUT;
- Motion Detection, Privacy Mask, OSD;
- RTSP and Onvif 2.6 compatible
- H.265/HEVC Main Profile/High Profile; H.264 Main Profile/High Profile
- Easy-to-use P2P Cloud service
- Multi web browser, PC Client, mobile APP remote access
- Lightning protection 4000V
- PoE 802.3af
- IP66, IK10
- 24pcs SMD IR Led, IR distance up to 40m
- HD 2.8-12mm varifocal lens
- Junction Box (Optional)


Technical Specifications

Camera	
Image Sensor	1/3" Progressive Scan CMOS
Effective Pixels	2560 x 1440
Electronic Shutter	AUTO, 1/25s ~ 1/100000s
Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
IR Led	24pcs SMD IR Led

IR Distance	Up to 40m
Focal length	2.8-12mm varifocal lens
Video	
Video Standard	H.265/H.264
Video Resolution	Main Stream: 25FPS 4mp @2560×1440, 30FPS 3mp @(2304×1296,1080P,720P Sub Stream: 640x360/D1/640*480 @25fps/30fps
Video Bitrates	32Kbps - 8Mbps, VBR/CBR
Day/Night	Auto/Color/(B/W)/Timing
WDR	D-WDR/HDR
White Balance	Auto/Indoor/Outdoor
AGC/BLC/HLC	Support
DNR	2D/3D DNR
OSD Overlay	Title and Time overlay
Other	Motion Detection, Privacy Mask, Mirror, Flip
Audio	
Audio Standard	G.711-u/G.711-a
Mic	Optional
Network	
Protocol	HTTP/RTSP/FTP/SMTP/DHCP/NTP/NFS, etc.
P2P	Yes
Web	IE, Firefox esr, etc.
Media	CMS, Android, IOS
Storage	FTP; NAS
ONVIF	17.06 compatible
General	
Network Port	1-RJ45, 100Mbps,
Power Supply	12 VDC ± 10%, PoE(802.3af)
Power Consumption	< 6W

Operating Temp.	-30°C -(+60)°C, 10%-90%RH
-----------------	---------------------------

▪ Dimensions (mm)



C

▪ Accessories



Junction Box GW-FSH-08A,



Bracket GW-J15-04A