

- 6MP Smart Dual Light Eyeball IP Camera with Microphone
- GW-HDB97RC86-ZP-DL



Features

- 1/2.8" Sony CMOS Sensor
- 6MP HD resolution 3072 x 2048 @25fps output
- Low illumination 0.01Lux
- Day/Night, AWB/MWB, BLC, HLC, 2D/3D-DNR, Shutter, IR-CUT
- D-WDR, Mirror, rotate, Defogging
- Built-in warm light and IR LED,
- Full-color image when detect human moving.
- Built in Microphone
- IR distance: up to 30m
- Material: Metal, IP66, PoE
- 2.8mm/F1.6 lens
- Popular Dome Camera, Easy to install



Technical Specifications

Camera	
Image Sensor	1/2.8" Sony CMOS Sensor
Effective Pixels	3072 x 2048

Electronic Shutter	AUTO, 1/25s ~ 1/100000s
Min. Illumination	0.01Lux@F1.0(AGC ON), 0Lux IR on
IR Led	Built-in warm light and IR LED
IR Distance	Up to 30m
Focal length	2.8mm fixed lens @F1.6
Video	
Video Standard	H.265/H.264
Video Resolution	Main Stream: 25fps@6MP(3072x2048)/5MP(2592x1944), 30fps@4MP/3MP/1080P/720P Sub stream: 30fps@D1/VGA/360P/CIF, etc.
Video Bitrates	32Kbps - 8Mbps, VBR/CBR
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR
White Balance	Auto/Indoor/Outdoor
AGC/BLC/HLC	Support
DNR	2D/3D DNR
OSD Overlay	Title and Time overlay
Other	Human Body detection, Motion Detection, Privacy Mask, Mirror, Flip
Audio	
Audio Standard	G.711-u/G.711-a
Microphone	Yes
Network	
Protocol	HTTP/RTSP/FTP/SMTP/DHCP/NTP/NFS, etc.
P2P	Yes
Web	IE, Firefox esr, etc.
Media	CMS, Android, IOS
Storage	FTP; NAS
ONVIF	17.06 compatible
General	

Network Port	1-RJ45, 100Mbps,
Power Supply	12 VDC $\pm$ 10%, PoE(802.3af)
Power Consumption	< 8W
Operating Temp.	-30°C-(+60)°C, 10%-90%RH

▪ Dimensions (mm)



- Accessories



Junction Box GW-FSH-06A,



Bracket GW-J15-03A