

- 2MP 4X Mini IR Bullet PTZ IP Camera
- GW-HW40RC80PT-LMP



- Features**
 - 2MP resolution
 - 4x 2.8-12mm motorized lens
 - Day/Night, AWB/MWB, BLC, HLC, 2D/3D-DNR, Shutter, IR-CUT
 - D-WDR, Mirror, rotate, Defogging
 - Multiply Style OSD Overlay, Motion Detection, Privacy Mask
 - Support RTSP and ONVIF
 - Easy-to-use P2P Cloud service
 - Compatible with Hikvision/Dahua/TVT/Uniview NVR
 - H.264/H.265 dual-stream media server
 - Lightning protection 6000V
 - Strong water-proof housing IP66
 - 6 pcs SMD IR Led, IR distance 30meters
 - Wall & Ceiling mount bracket all-in-one

Technical Specifications

Camera	
Image Sensor	1/2.8" Sony Low light CMOS sensor
Effective Pixels	1945 (H) × 1097 (V)
Electronic Shutter	AUTO, 1/25s ~ 1/100000s
Min. Illumination	0.001Lux@F1.2(AGC ON), 0Lux IR on
IR Led	6 pcs SMD IR Led
IR Distance	Up to 30m
Focal length	4X zoom. HD 2.8-12mm motorized lens

Video	
Video Standard	H.265/H.264
Video Resolution	Main Stream: 1-30fps@2MP(1920x1080P); 1-30fps@720P Sub Stream: D1/VGA(640x480)/360P/QVGA@30fps
Video Bitrates	32Kbps - 8Mbps, VBR/CBR
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR
White Balance	Auto/Indoor/Outdoor
AGC/BLC/HLC	Support
DNR	2D/3D DNR
OSD Overlay	Title and Time overlay
Other	Human Body detection, Motion Detection, Privacy Mask, Mirror, Flip
PTZ	
Horizontal Range	0° ~ 180°
Vertical Range	-0.5° ~ 55°
Preset Point	1
Horizontal Rotation Speed	0.5°~20°/s
Vertical Rotation Speed	0.5°~10°/s
Guard Position	Support
Power-off Recovery	Support
Audio	
Audio Standard	G.711-u/G.711-a
Mic	Optional
Network	
Protocol	HTTP/RTSP/FTP/SMTP/DHCP/NTP/NFS, etc.
P2P	Yes
Web	IE, Firefox esr, etc.
Media	CMS, Android, IOS

Storage	FTP; NAS
ONVIF	17.06 compatible
General	
Network Port	1 - RJ45, 100Mbps,
Power Supply	12 VDC $\pm$ 10%, PoE(802.3af)
Power Consumption	< 15W
Operating Temp.	-30°C -(+60)°C, 10%-90%RH

▪ Dimensions (mm)

